



SHELVING

AMCO II® WIRE SHELVING



ITEM # _____ MODEL # _____ QTY: _____
 PROJECT: _____
 OPTIONS: YES _____ NO _____



Standard Features & Benefits

- ◆ Unique square post design uses 27% more steel providing greater strength and durability than typical round post systems
- ◆ Shelves come in 5 widths and 8 lengths
- ◆ Shelves up to 48" long support up to 1,000 lbs. (450 kg)
- ◆ Assembly is fast and easy with a one-piece shelf installation adapter — a collet that can be slipped on the post at any height
- ◆ Posts are notched on 2" centers to assure perfect shelf alignment every time
- ◆ 17% taller collar provides more strength and greater rigidity
- ◆ Solid 2-1/8" robotic welds provide more stability than the two spot welds used on round post systems
- ◆ Shelf wire averages 50% thicker than other systems providing greater shelf capacity and strength
- ◆ Shelves have solid edges instead of truss edges making them easier to clean and label
- ◆ Use add-on unit to continue a straight line of shelving, for right angles or for back-to-back shelving
- ◆ Frame is 12 gauge solid steel
- ◆ Choose finish or color by adding appropriate suffix to model number (see chart to the left)

*Select a finish. Add suffix to model number.

Finish	Suffix	Color	Suffix
Plating Plus™	CP	Black**	BK
Polygard® (Blue)	PG	White**	W
Stainless Steel	SS	Red**	R

**Minimum quantity must be ordered for shelving with color finishes. Any combination of shelves and posts must equal 100. (For example, 40 posts and 60 shelves.)

For SPG's complete product menu, visit www.spgusa.com or call 877.503.4SPG (4774)



SHELVING

AMCO II WIRE SHELVING

Specifications

SHELVES

Shelves are constructed of .162" gauge crosswires spaced 1-1/16" on centers with 5/16" (.3125") cross-braces. Cross braces are welded at each end of 9/16" x 1-1/4" x .090" leg. Square tapered 1-3/4" high steel collars are welded at each corner and a series of .262" rebrace wires are welded to the underside of the 18", 21" and 24" wide shelves in lengths of 54" and longer. All contact points are welded.

POSTS

Posts are constructed of .065" thick square tubes notched every 2" on each corner. A nylon cap is installed on the top and a nylon housing for a 3/8" – 16 x 1-1/4" steel leveler is notched on the bottom. The leveler has a 7/8" hex head and a 3/4" threadless shoulder to eliminate deposits of mop strands and broom fibers.

ASSEMBLY

Four nylon tapered collets are packed with each shelf. The collets can be installed onto any notched position on the post. The tapered shelf collars mate to the tapered nylon collet to securely seat the shelf onto the post. No additional tools are needed for assembly.

Model No.*	W x L		Weight	
	(In.)	(mm.)	(Lbs.)	(Kg.)
12" Wide Shelves				
A1224	12 $\frac{1}{4}$ x 23 $\frac{3}{4}$	305 x 610	6 $\frac{1}{2}$	2.9
A1230	12 $\frac{1}{4}$ x 29 $\frac{3}{4}$	305 x 760	7 $\frac{1}{2}$	3.4
A1236	12 $\frac{1}{4}$ x 35 $\frac{3}{4}$	305 x 915	9	4.1
A1242	12 $\frac{1}{4}$ x 41 $\frac{3}{4}$	305 x 1065	10 $\frac{1}{2}$	4.5
A1248	12 $\frac{1}{4}$ x 47 $\frac{3}{4}$	305 x 1220	12	5.4
A1254	12 $\frac{1}{4}$ x 53 $\frac{3}{4}$	305 x 1370	13 $\frac{1}{2}$	5.9
A1260	12 $\frac{1}{4}$ x 59 $\frac{3}{4}$	305 x 1525	14	6.3
A1272	12 $\frac{1}{4}$ x 71 $\frac{3}{4}$	305 x 1830	15 $\frac{1}{2}$	7
15" Wide Shelves				
A1524	15 $\frac{1}{4}$ x 23 $\frac{3}{4}$	380 x 610	7 $\frac{1}{2}$	3.4
A1530	15 $\frac{1}{4}$ x 29 $\frac{3}{4}$	380 x 760	8 $\frac{1}{2}$	3.9
A1536	15 $\frac{1}{4}$ x 35 $\frac{3}{4}$	380 x 915	10	4.5
A1542	15 $\frac{1}{4}$ x 41 $\frac{3}{4}$	380 x 1065	11 $\frac{1}{2}$	5.2
A1548	15 $\frac{1}{4}$ x 47 $\frac{3}{4}$	380 x 1220	13 $\frac{1}{2}$	6.1
A1554	15 $\frac{1}{4}$ x 53 $\frac{3}{4}$	380 x 1370	14 $\frac{1}{2}$	6.6
A1560	15 $\frac{1}{4}$ x 59 $\frac{3}{4}$	380 x 1525	16	7.3
A1572	15 $\frac{1}{4}$ x 71 $\frac{3}{4}$	380 x 1830	19	8.6
18" Wide Shelves				
A1824	18 $\frac{1}{4}$ x 23 $\frac{3}{4}$	455 x 610	8 $\frac{1}{2}$	3.6
A1830	18 $\frac{1}{4}$ x 29 $\frac{3}{4}$	455 x 760	9 $\frac{1}{2}$	4.3
A1836	18 $\frac{1}{4}$ x 35 $\frac{3}{4}$	455 x 915	11	5
A1842	18 $\frac{1}{4}$ x 41 $\frac{3}{4}$	455 x 1065	13 $\frac{1}{2}$	5.9
A1848	18 $\frac{1}{4}$ x 47 $\frac{3}{4}$	455 x 1220	15	6.8
A1854	18 $\frac{1}{4}$ x 53 $\frac{3}{4}$	455 x 1370	16 $\frac{1}{2}$	7.5
A1860	18 $\frac{1}{4}$ x 59 $\frac{3}{4}$	455 x 1525	18	8.2
A1872	18 $\frac{1}{4}$ x 71 $\frac{3}{4}$	455 x 1830	21 $\frac{1}{2}$	9.7
21" Wide Shelves				
A2124	21 $\frac{1}{4}$ x 23 $\frac{3}{4}$	535 x 610	9	4.1
A2130	21 $\frac{1}{4}$ x 29 $\frac{3}{4}$	535 x 760	10 $\frac{1}{2}$	4.8
A2136	21 $\frac{1}{4}$ x 35 $\frac{3}{4}$	535 x 915	12	5.4
A2142	21 $\frac{1}{4}$ x 41 $\frac{3}{4}$	535 x 1065	15 $\frac{1}{2}$	6.8
A2148	21 $\frac{1}{4}$ x 47 $\frac{3}{4}$	535 x 1220	17	7.7
A2154	21 $\frac{1}{4}$ x 53 $\frac{3}{4}$	535 x 1370	19 $\frac{1}{2}$	8.8
A2160	21 $\frac{1}{4}$ x 59 $\frac{3}{4}$	535 x 1525	20 $\frac{1}{2}$	9.3
A2172	21 $\frac{1}{4}$ x 71 $\frac{3}{4}$	535 x 1830	24	10.9
24" Wide Shelves				
A2424	24 $\frac{1}{4}$ x 23 $\frac{3}{4}$	610 x 610	10	4.5
A2430	24 $\frac{1}{4}$ x 29 $\frac{3}{4}$	610 x 760	12 $\frac{1}{2}$	5.4
A2436	24 $\frac{1}{4}$ x 35 $\frac{3}{4}$	610 x 915	13 $\frac{1}{2}$	6.1
A2442	24 $\frac{1}{4}$ x 41 $\frac{3}{4}$	610 x 1065	16 $\frac{1}{2}$	7.5
A2448	24 $\frac{1}{4}$ x 47 $\frac{3}{4}$	610 x 1220	18 $\frac{1}{2}$	8.4
A2454	24 $\frac{1}{4}$ x 53 $\frac{3}{4}$	610 x 1370	21 $\frac{1}{2}$	9.5
A2460	24 $\frac{1}{4}$ x 59 $\frac{3}{4}$	610 x 1525	23	10.4
A2472	24 $\frac{1}{4}$ x 71 $\frac{3}{4}$	610 x 1830	27	12.2

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke

SPG International, LLC
11230 Harland Drive NE
Covington, GA 30014
877-503-4SPG (4774)

www.spgusa.com

The best names in the business
all have one thing in common.

EXPECT MORE
SPG
STORAGE PRODUCTS GROUP