

## **CANTILEVER RACKS**

### **BUTTON-ON® MEDIUM DUTY CANTILEVER RACKS**

# GILLIS-JARKE by







ITEM #	MODEL #	QTY:
PROJECT:		
OPTIONS:□YES	□NO	

### **Standard Features & Benefits**

- Button-On lets you load up to 2,000 lbs. at one time
- Ideal for storing pipe, tubing, lumber and bar stock
- ◆ 700 to 1,000 lb. load capacity per arm
- 12,000 lb. load capacity per column per side
- Adjustable unit assembles into continuous system for growth
- Arms 'button' into position & adjust on 4" centers
- Unique inclined arm with 18 degree slope, buttons in place
- Available in starter or add-on units



## **CANTILEVER RACKS**

### BUTTON-ON® MEDIUM DUTY CANTILEVER RACKS

#### Starter and Add-On Units

Height (Ft.)	Arm Length	Capacity Per Arm (Lbs.)	Base Length (In.)	No. Of Arms	Brace Set Width	Capacity Per Unit (Lbs.)	Starter Model No.	Wt. (Lbs.)	No. Of Arms	Add-On Model No.	Wt. (Lbs.)
Single Co	lumn Unit										
7	12" inclined	1000	261/2	12	6'	12,000	CR-1	314	6	CR-1A	182
7	12" straight	1000	261/2	12	6'	12,000	CR-2	314	6	CR-2A	182
7	16" inclined	1000	261/2	12	6'	12,000	CR-5	332	6	CR-5A	191
7	16" straight	1000	261/2	12	6'	12,000	CR-6	332	6	CR-6A	191
10	20" straight	850	341/2	20	6'	17,000	CR-9	455	10	CR-9A	257
10	24"straight	700	341/2	20	6'	14,000	CR-10	485	10	CR-10A	277
Double C	olumn Unit										
7	12" inclined	1000	45	24	6'	24,000	CR-3	406	12	CR-3A	228
7	12" straight	1000	45	24	6'	24,000	CR-4	406	12	CR-4A	228
7	16" inclined	1000	45	24	6'	24,000	CR-7	442	12	CR-7A	246
7	16" straight	1000	45	24	6'	24,000	CR-8	442	12	CR-8A	246
10	20" straight	850	61	40	6'	34,000	CR-11	687	20	CR-11A	371
10	24" straight	700	61	40	6'	28,000	CR-12	747	20	CR-12A	401

#### Columns

Height (Ft.)	Arm Length	Base Length (In.)	Capacity Per Side (Lbs.)	Maximum Arms	Model No.	Wt. (Lbs.)
Columns 5	Single Side	ed				
7	12", 16"	261/2	6,000	6	CR-61-A	105
7	20", 24"	341/2	4,200	6	CR-61-AL	111
10	12", 16"	261/2	9,000	9	CR-101-A	120
10	20", 24"	341/2	7,650	9	CR-101-AL	127
Columns I	Double Sid	led				
7	12", 16"	45	6,000	6	CR-61-B	124
7	20", 24"	61	4,200	6	CR-61-BL	136
10	12", 16"	45	9,000	9	CR-101-B	140
10	20", 24"	61	7,650	9	CR-101-BL	156

#### Arms

Arms Length (ln.)	Capacity Per Arm (Lbs.)	Model No.	Wt. (Lbs.)
Straight Arms			
12	1,000	CR-60-C3	4 <sup>1</sup> / <sub>2</sub>
16	1,000	CR-60-D3	6
20	850	CR-60-E3	8
24	700	CR-60-F3	91/2
Inclined Arms			
12	1,000	CR-60-C1	41/2
16	1,000	CR-60-D1	6

#### Pans for Arms

Pan Length*	Arm Description	Arm Length	Model No. (Add Prefix CR-60	
(Ft.)	Arm Description	Arm Length	To Model No.)	
5'	Straight No Lip	12" / 16" / 20" / 24"	112C2 / I16D2 / I20E2 / I24F2	
5'	Straight With Lip	12" / 16" / 20" / 24"	12C3 /  16D3 /  20E3 /  24F3	
5'	Inclined No Lip	12" / 16"	12C4/ 16D4	
5'	Inclined With Lip	12" / 16"	l12C1 / l16D1	
8'	Straight No Lip	12" / 16" / 20" / 24"	J12C2 / J16D2 / J20E2 / J24F2	
8'	Straight With Lip	12" / 16" / 20" / 24"	J12C3 / J16D3 / J20E3 / J24F3	
8'	Inclined No Lip	12" / 16"	J12C4 / J16D4	
8'	Inclined With Lip	12" / 16"	J12C1 / J16D1	

#### **Brace Sets**

Model No.	Wt. (Lbs.)	Width	Height
CR-61-EF	18	3'	7'
CR-61-GH	50	6'	7′
CR-61-JK	63	8'	7'
CR-101-GH	55	6'	10'
CR-101-JK	67	8'	10'

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke

SPG International, LLC 11230 Harland Driv e NE Cov ington, GA 30014 877-503-4SPG (4774) The best names in the business all have one thing in common.

